




Alliance

*FOUR-WAY COMPACT CASSETTE
12 000 Btu (CSU2-12CCA) & 18 000 Btu (CSU2-18CCA)*



- 
- *Cooling and heating*
 - *4-way airflow*
 - *Extremely quiet*
 - *Backed nationwide
by Alliance*

FOUR-WAY COMPACT CASSETTE


12 000 Btu (CSU2-12CCA) & 18 000 Btu (CSU2-18CCA)



Technical Data

Model - Indoor			CSU2-12CCA	CSU2-18CCA
Function			Cooling/heating	Cooling/heating
Power supply		V-Ph-Hz	220~240-1-50	220~240-1-50
Cooling	Capacity	Btu/h	12000	18000
	Input	W	1170	1956
	EER	W/W	2.73	2.71
Heating	Capacity	Btu/h	13000	20000
	Input	W	1286	1905
	COP	W/W	3.11	3.15
Air flow (Hi/Med/Lo)		m³/h	650/560/450	810/720/580
Noise level (Hi/Med/Lo)		dB/(A)	42/38/33	48/44/38
Indoor Unit	WxDxH (body)	mm	570x570x260	570x570x260
	Packing WxDxH (body)	mm	655x655x290	655x655x290
	WxDxH (panel)	mm	647x647x50	647x647x50
	Packing WxDxH (body)	mm	715x715x123	715x715x123
	Weight Net/Gross	kg	16/19	19/21
Refrig. piping	Liquid/ gas side	mm	Ø6.4/Ø12.7	Ø6.4/Ø12.7
OUTDOOR				
Power supply		V-Ph-Hz	220~240-1-50	220~240-1-50
Max. input consumption		W	1950	2950
Max. input current		A	8.9	15.0
Outdoor air flow		m³/h	1840	2200
Outdoor noise level		dB(A)	43	56
Dimension (WxDxH)		mm	780x250x547	760x285x590
Packing (WxDxH)		mm	910x335x575	887x355x645
Net/Gross Weight		kg	32/34	38.5/41
Refrigerant type			R22	R22
Charged volume		kg	0.85	1.4
Design pressure		MPa	2.6/1.0	2.6/1.0
Refrig. piping	Liquid/gas side	mm	Ø6.4/Ø12.7	Ø6.4/Ø12.7
	Max. pipe length	m	15	30
	Max. level diff.	m	8	10
Ambient temp. (Cooling/heating)		°C	21~43/-5~24	21~43/-5~24

Features



Alliance reserves the right to discontinue or change specifications or design at any time without notice and without incurring obligation.

Sold, distributed and nationally supported by Alliance at:

Gauteng: (011) 704-6320

Cape Town: (021) 556-8292

Port Elizabeth: (041) 484-6413

Pretoria: (012) 643-0445

Kwa-Zulu Natal: (031) 579-1895